

JS005831588A

United States Patent [19]

Hotto

[45] Date of Patent:

[11]

Patent Number:

5,831,588

*Nov. 3, 1998

[54]	DC INTEGRATING DISPLAY DRIVER
	EMPLOYING PIXEL STATUS MEMORIES

[76] Inventor: Robert Hotto, 3109 Evening Way, La

Jolla, Calif. 92037

[*] Notice: The term of this patent shall not extend

beyond the expiration date of Pat. No.

5,280,280.

[21] Appl. No.: 803,059

[22] Filed: Feb. 20, 1997

Related U.S. Application Data

[63] Continuation of Ser. No. 446,898, May 17, 1995, Pat. No. 5,627,558, which is a continuation of Ser. No. 88,256, Jul. 7, 1993, Pat. No. 5,444,451, which is a continuation of Ser. No. 705,190, May 24, 1991, Pat. No. 5,280,280.

[51]	Int. Cl.°	
F = 0.1	TT 0 01	A 4 = 14 0 0 A 4 = 10 0

[52] **U.S. Cl.** **345/100**; 345/98

[56] References Cited

U.S. PATENT DOCUMENTS

5,444,457	8/1995	Hotto	345/94					
5,485,173	1/1996	Scheffer et al	345/100					
5,627,558	5/1997	Hotto	345/94					
FOREIGN PATENT DOCUMENTS								

FOREIGN PATENT DOCUMENTS

2-113476	9/1990	Japan	 345/148
2-113477	9/1990	Japan	 345/148

OTHER PUBLICATIONS

A Generalized Addressing Technique for RMS Responding Matrix LCDs, T.N. Ruckmongathan, pp. 80–85, 1988 IEEE.

Primary Examiner—Jeffery Brier Attorney, Agent, or Firm—John L. Rogitz

[57] ABSTRACT

This invention relates to an improved drive and control means for matrix addressable electro-optic displays, such as passive matrix LCDs and active matrix LCDs. The present invention achieves improved drive and control of displays through the use of real time computation and memory circuits to simulate the electro-optic condition and the accumulated DC bias of individual display elements. This eliminates the burden of frequent and symmetrical reversals of the drive polarity, and allows the implementation of flexible DC drive methodologies.

31 Claims, 7 Drawing Sheets

